

# PEARL LUSTRE INTERIOR WALL FINISH

Pearl Lustre is a solvent-based paint specially formulated based on special resins and pigment for interior applications. Pearl like lustre is the unique feature of this finish paint. It is suitable for interior cement plastered wall, wooden / hard board surfaces, ceilings etc. It is ideal for hard working areas like kitchens, bathrooms, corridors etc. Pearl Lustre finish is washable and retains its pearl like lustre finish for years.



## TECHNICAL DATA

<b>Areas of Application</b>	:	Cement Plastered surfaces, walls, ceilings, primed wood surfaces
<b>Viscosity of Supply</b>	:	100 ± 10 sec / b4 / 30°C
<b>Method of Application</b>	:	Brush / Roller / Spray
<b>Recommended Primers for Cement Plaster</b>	:	British Paints Solvent thinnable Primer minimum 2 Coats
<b>For Wood</b>	:	British Paints Wood Primer Pink or White
<b>Thinner Recommended</b>	:	British Paints Synthetic Thinner
<b>Application viscosity</b>	:	Supply viscosity can be thinned with 2-3% of recommended thinner
<b>For brushing</b>	:	(if necessary) depending on surfaces
<b>For spraying / roller</b>	:	Application viscosity is to be adjusted with recommended thinner
<b>Covering Capacity</b>	:	120-140 sq. ft. / ltr / 2 coats (Spreading by brush on smooth surface)
<b>Drying Time</b>	:	Surface Dry maximum 4 Hrs.(28-30°C & 60 ± 5% R.H.) Hard Dry 24 Hrs.
<b>Finish</b>	:	Smooth lustre like finish
<b>Flash Point</b>	:	Above 35°C
<b>Shades</b>	:	White & Base White
<b>Packs available</b>	:	20 ltr, 10 ltr, 4 ltr & 1 ltr

## DIRECTIONS FOR USE

Ensure the surface free from loose particles, dirt, dust, grease, oil, moisture, etc. Surfaces previously painted with oil bound distemper, flat oil paint, emulsion paint etc. are in sound condition, are to be thoroughly sanded with emery paper No. 280-300 to dull Matt for proper adhesion. If surfaces are previously painted with dry distemper (lime wash) or ordinary distemper (chalking out), the coats are to be completely scraped off. Wash with water and dry. Apply two coats of recommended primer with interval of minimum 18 hrs. between coats. Sand with emery paper no. 300-320 and apply two coats of Pearl Lustre with an interval of minimum 18 hrs. between the coats.

(The information herein is given in good faith. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface).

### Special Features

Washable | Ideal for hard working areas like Kitchen, Bathrooms, Corridors etc.  
Available in White, Base White & 9 Tinting Bases



PEARL LUSTRE INTERIOR WALL FINISH