

WOOD GRAIN NC SANDING SEALER

British Paints NC Sanding Sealer is a fast drying, high-fill clear sealer which effectively seals & fills pores in wood & enhances aesthetics of wood. It is easy to sand and also strengthens adherence of top coat application. It is suitable for interior wooden surfaces.

DIRECTIONS FOR USE

SURFACE PREPARATION: For Pre-Polished Wood remove all existing coats by sanding or scrapping. For New Wood sand surface smooth using emery paper No. 180 followed by 320/ 400. Remove loose dust particles, grease etc.

Uneven Surfaces, Small Pits or Cracks to be made even by applying a filler coat & allow drying for an hour there after sand off with emery paper no. 180 followed by 320.

APPLICATION OF SANDING SEALER: Thin 1 part of British Paints NC Sanding Sealer with 2 parts of NC Thinner. If applications by muslin cloth then apply sealer at least for 8-10 passes for proper finish. In case of spray, apply 2-3 coats. Sand the dried surface with emery paper No. 220. Additional coats may be applied if required. The dry surface is now ready for applying a top coat.

(The information herein is given in good faith. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface).



WOOD GRAIN NC SANDING SEALER

Special Features

- Easy to Apply | Enhances Aesthetics of Wood | Provides Smoothness to Wood

