WOOD GRAIN MELAMINE 2K System

Wood Grain Melamine Wood Finish is a premium quality melaminised coating specially formulated as a protective and decorative clear coating finish for wood. It protects the wood for many year from heat, water, insect attack etc. It has got excellent resistance to staining from oils, food and hot beverages. It is best suitable for interior application. It offers substantial economy in terms of durability, decorative and protective value compared to other conventional coating.



SALIENT FEATURES







Excellent Durability



Stain Resistant



Low Odour

TECHNICAL DATA

SURFACE PREPARATION

Sand surface with emery paper No. 180 followed by No. 320. Clean surface free of dust and grease. Apply Wood Grain wood filler using muslin cloth of putty knife. Remove excess filler. Allow it to dry for 2-3 hours. Filled surface should be sanded with Emery No. 180 followed by No. 320. Repeat filling operation if necessary.

WOOD GRAIN MELAMINE (2 pack)

This is a two – pack system. Take by volume 90 parts base & IO parts hardner from the accompanying plastic bottle and mix them in a glass / plastic enamelled container. Stir the mixture and allow to mature for 30 minutes. Strain through muslin cloth and use before 8 hours. Spraying is done at a viscosity of 25 - 30 second and at a pressure of 2.1 kg / sq cm. Brush or spray wood Grain natural wood finish clear sealer and dry 22- 24 hours. Sand with Emery No. - 320 and wipe off loose dust. Brush or spray Wood Grain natural wood finish matt or glossy at an inter coat interval of 6 hours if brushed and half hour if sprayed. After drying for 24 hours, sanding and buffing will enhance the glossy finish substantially. Buffing is not done if Matt Finish is desired.

Packs available: 20 ltr, 4 ltr & 1 ltr



Interior



Stir & Strain



Brush



Spray

