

Acrylic Exterior Wall Primer

Exterior wall primer is a water based wall coating suitable for application on exterior as an intermediate coat to exterior emulsions.

PERFORMANCE FEATURES & BENEFITS

Exterior wall primer has good opacity and whiteness, which helps improve the appearance of the emulsion topcoats. Exterior Wall Primer does not chalk and can be applied on freshly plastered surfaces that are adequately cured. Exterior Wall Primer does not require any water curing.

RECOMMENDED USAGE

Exterior Wall Primer can be applied on wide range of exterior cement plasters, exterior ceilings, asbestos sheets, concrete etc as an undercoat.

RECOMMENDED APPLICATION

Cleaning: ensure that the surface to be painted is free from any loose paint, dust or grease. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.

Filling: Application of any kind of putty is not recommended. Surface imperfections such as holes, dents, cracks are to be filled only by using mixture of white cement & fine sand (in the ratio 1:3)

Freshly plastered surfaces must be allowed to cure completely.

TECHNICAL DATA

Thinner	: Water
Dilution	: 90-110
Recoating Period	: 4 hrs
Coverage	: 1 On normal masonry surface by brushing coat 12-14 sq.mt/ltr
Drying time	: Surface Dry Time – 30 minutes
Gloss levels / Sheen Levels	: NA
Shell life	: 3 years from date of manufacture in original tightly closed Containers away from direct sunlight & excessive heat.



Acrylic Exterior Wall Primer

**Actual coverage may vary from quoted due to factors such as method and condition of application and surface roughness.

