



# ALL ROUNDER PRIMER



British Paints All Rounder Primer is an emulsion based water thinnable primer that is specially designed for application on the exterior as well as interior masonry surfaces available in white shade. It can also be applied to a wide range of cement plasters, ceilings, asbestos sheets, concrete, etc. as an undercoat. Applied by brush or roller with covering capacity of 120-140 Sq Ft/Ltr./Coat. Its surface drying time is within 1 hour and hard dry within 24 hours. Recoating period for British Paints All Rounder wall primer is 5-6 hours.

## PRODUCT FEATURES



### PACKS AVAILABLE



## HOW TO APPLY

### DIRECTIONS FOR USE ON INTERIORS

#### **SURFACE PREPARATION:**

Sand the surface with emery paper no. 180 to remove loose particles, paint, dust, cracked and flaking paint, and wipe clean.

#### **PRIMER:**

Apply a coat of British Paints All Rounder Primer by thinning with water in the ratio of 1:1 by volume and allow drying for 6-8 hours.

#### **PUTTY:**

Smoothen the surface by filling dents with a thin coat of British Paints Acrylic Wall Putty and allow drying for 4-6 hours. Sand the surface with emery paper no. 180 and wipe clean.

#### **PRIMER:**

Apply another coat of British Paints All Rounder primer and allow drying for 5-8 hours. Before application of topcoat, sand the surface with emery paper no. 320 and wipe clean.

### DIRECTIONS FOR USE ON EXTERIORS

#### **SURFACE PREPARATION:**

Ensure that the surface to be painted is thoroughly clean, dry, and free from all loose dirt, chalk, grease, fungi, algae, and flaking paint. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing & cleaning with water. Freshly plastered surfaces must be cured completely.

#### **PUTTY:**

Surface imperfections like holes, dents, and cracks are to be filled with British Paints Shield/ British Wall Putty.

#### **PRIMER:**

Apply one coat of British Paints All Rounder Primer by thinning with water in the ratio of 1:1 by volume. Before application of topcoat, allow the primer to dry for at least 4-5 hours.

STIR WELL BEFORE USE. KEEP THE CONTAINER CLOSED WHEN NOT IN USE.

(The information herein is given in good faith. Covering capacity is indicated on the basis of results obtained on a prepared smooth & non absorbing surface.)

(Please note that this product technical data sheet supersedes all previous versions.)

### FOR MORE ENQUIRY

19 D.D.A. Commercial Complex, Kailash Colony Extn. Zamrudpur, New Delhi-110048  
Ph.: 011- 29240394-0396, 29231992, E-mail: [atyourservice@britishpaints.in](mailto:atyourservice@britishpaints.in)

TOLL FREE ☎ 1800-111-300 | 📞 +91 8882022255 | [www.britishpaints.in](http://www.britishpaints.in)

Also Follow us on — BritishPaints | British\_Paints | company/British-Paints