

GLO ADVANCED ENAMEL

British Paints Glo Advanced Enamel, first quality enamel is specially formulated for the discerning customer who does not settle for anything less in life. The product has a smooth and uniform finish with excellent leveling and hard mirror like gloss that resists the vagaries of nature like water, sunlight and moisture. Its brushability is excellent. Glo Advanced Enamel is made tough for exterior use to withstand rugged conditions. It is used and recommended for finishing doors, windows, furniture and fixtures. Keeping outer activities in mind, it is ideal for hoardings, signboards, railway rolling stock, truck fleets, transport coaches, machinery and equipment and a variety of other articles. Glo Advanced colours are specially formulated shades for use on doors, windows, fixtures, furniture etc. It's whiteness retention property is outstanding.



TECHNICAL DATA

Areas of Application	:	Metals, Wood, Plaster and variety of other surfaces
Viscosity of Supply	:	For Whites - 100 ± 10 Secs by Ford Cup B4 For Shades - 95 ± 5 Secs at 30°C
Thinner Recommended	:	British Synthetic Thinner
Recommended Primers	:	
For Metal	:	British Paints Red Oxide Primer British Paints Solvent Thinnable White Primer
For Wood	:	British Paints Wood Primer - Pink or White
For Plaster	:	British Paints Cement Primer Solvent Thinnable
For Non-ferrous or Galvanised Surface	:	British Paints Zinc Chromate Primer
Method of Application	:	Brush / Roller / Spray - for brushing supply viscosity can be thinned with 1 to 2% thinner if necessary. For spray and roller application viscosity is to be adjusted to appropriate level with recommended thinner
Covering Capacity	:	205-225 sq. ft. / ltr / coat (at 20-25 Microns dry film thickness)
(Spreading by brushing on Smooth Mild Steel Surface)	:	110-130 sq. ft. / ltr / 2 coats (at 35-40 microns dry film thickness)
Drying Time	:	Surface dry - Not more than 4 Hrs. (@ 28-30°C & 60 ± 5% R.H.) Hard Dry - Not more than 18 Hrs.
Finish	:	Smooth & Glossy
Shelf Life	:	3 years from date of manufacture in original tightly closed containers kept away from direct sunlight and excessive heat
Flash Point	:	Above 35°C (86°F) (Abel's closed cup)
Shades Available	:	As per Shade Card
Packs Available	:	20 ltr, 10 ltr, 4 ltr, 1 ltr, 500 ml, 200 ml, 100 ml & 50 ml

DIRECTIONS FOR USE

The surface to be painted should be dry and free from rust, grease, oil, free from loose matter. Degreasing and de-rusting can be done by suitable treatment if necessary. In case of new or bare surfaces, it should be applied over an appropriate primer. Use of Knifing Paste Filler is recommended, if necessary to fill up dents and any surface imperfections. This should be used after sanding the first primer coat. If Knifing paste Filler is used, then one coat of British Paints Solvent Thinnable Primer Surfacer grey or white is to be applied after drying for 10 hrs. Apply Glo Advanced Enamel using recommended thinner. For best results, two coats of Glo Hi Gloss Enamel are recommended giving 18 hrs of drying between the coats.

(The information herein is given in good faith. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface).

