



# MASTER BLASTER SMART INTERIOR EMULSION



**WATER BASED**

British Paints Master Blaster Smart Interior Emulsion is a super quality Economy Water Thinnable coating for application on the interior surface and provides a rich smooth finish near to the price of Distemper. Master Blaster Smart outperforms conventional distempers in all respects be its durability, hiding, covering capacity, washability, finish, etc.

## PRODUCT FEATURES



### PACKS AVAILABLE



## HOW TO APPLY

Performance of British Paints Master Blaster Smart Interior Emulsion depends on surface preparation & application as outlined below.

### SURFACE PREPARATION

The newly plastered surface must be allowed to mature for a minimum period of six months. Rub the surface with emery paper no 180 to remove loose particles, paint, dust, cracked & flaked paint, and wipe clean. Oily or Greasy area to be wiped with mild soap solution followed by rubbing with a clean soft cloth and allow the surface to dry before priming.

### PRIMER

Apply a coat of British Paints Solvent Thinnable Primer or Water Thinnable Acrylic Cement Primer (For repainting use Water Thinnable Acrylic Cement Primer and for new surface Solvent Thinnable Primer is recommended) and allow drying for 6-8 hour.

### PUTTY

Smoothen the surface by filling dents with a thin coat of British Paints Acrylic Wall Putty and allow drying for 4-6 hours. Sand the surface with emery paper no. 180 and wipe clean

### PRIMER

Apply another coat of British Paints Solvent Thinnable Primer or Water Thinnable Acrylic Cement Primer and allow drying for 6-8 hours. Sand the surface with emery paper no.320 and wipe clean.

### TOP COAT

Thin 1 Liter of Master Blaster Smart Interior Emulsion with 500-600 ml of water. Apply 2-3 coats of this thinned paint with a gap of 4-5 hours in between two coats

### GUIDANCE FOR PROPER MAINTENANCE

For removing stains, clean the surface using a sponge with a mild soap solution. Once you finish, wipe the surface clean. Ensure a drying time of 1 week of the paint before cleaning with a soap solution.

(The information herein is given in good faith. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface)

(Please note that this product technical data sheet supersedes all previous versions.)

## FOR MORE ENQUIRY

19 D.D.A. Commercial Complex, Kailash Colony Extn. Zamrudpur, New Delhi-110048  
Ph.: 011- 29240394-0396, 29231992, E-mail: atyourservice@britishpaints.in

TOLL FREE 1800-111-300

+91 8882022255

www.britishpaints.in

Also Follow us on



BritishPaints



British\_Paints



company/British-Paints