

SHEER CLASS METALLICS ECO

Sheer Class Metallics Eco is a premium quality water based metallic finish paint which creates variety of effects on interior & exterior wall & is based on pure acrylic emulsion.



DIRECTION FOR USE

•SURFACE PREPARATION

Ensure that the surface to be painted is thoroughly clean , dry & free from all loose dirt , chalk , grease , fungi , algae and flaking paint etc.

PRIMER

Apply a coat of British Paints Solvent Thinnable or Water Thinnable Acrylic Cement Primer (in case of interiors) (for repainting use Water Thinnable Acrylic Cement Primer and for new surface Solvent Thinnable Primer is recommended) & water Thinnable Exterior Wall Primer (in case of Exteriors) & allow drying for 6-8 hours .

PUTTY

Surface imperfections like holes , dents and cracks are to be filled with British Paints British Wall Putty (in case of exteriors) or Acrylic Wall Putty (in case of Interiors) .However British Wall Putty can also be used for interiors as well .

PRIMER

Apply another coat of Primer & allow drying for 6-8 hours .

EMULSION (Base Coat)

Apply 2-3 coats of Sheer Class Splendor (in case of Interiors) or our any other premium interior Emulsion & Expa 7 (in case of Exteriors) or our any other premium Exterior Emulsion suitably .

SHEER CLASS METALLICS Eco (Top Coat)

Apply 1 coat of Sheer Class Metallics Eco with 200-300 ml dilution (max) as a top coat for either flat finish or use special effects tool to create desired pattern.

SHEER CLASS METALLICS ECO

