



SHINGAR ALL ROUNDER



Shingar All-Rounder is 100% Acrylic Emulsion based wall coating, suitable for both exterior & interior walls. It is reinforced with special silicon emulsion to offer outstanding water resistance and adhesion properties on all type of construction and residential buildings, offices and commercial complexes. It offers excellent anti-fungal properties with outstanding resistance to color fading. It provides soothing smooth finish on the walls. It also claims with 3 years performance warranty.

PRODUCT FEATURES



PACKS AVAILABLE



HOW TO APPLY

Surface Preparation :

Ensure that the surface to be painted is cleaned thoroughly with emery paper no.180 remove loose particles, dirt, chalk, grease, fungi & flaking paint. Any previous growth of fungus or moss needs to be removed thoroughly by vigorous wire brushing & cleaning with water. Freshly plastered surfaces should be painted with Shingar All rounder only after 2-3 months of curing of plaster.

For Interior Application:

Primer:

Apply a coat of British Paints Solvent Thinnable Primer or Water Thinnable Supra Acrylic Cement Primer (For repainting use water thinnable Supra Acrylic Cement Primer and for new surface Solvent Thinnable Primer is recommended) and allow drying 6 -8 hours.

Putty:

Smoothen the surface by filling dents with a thin coat of British Paints Acrylic Wall Putty and allow drying for 4-6 hours. Sand the surface with emery paper no.180 and wipe clean.

Primer:

Apply another coat of British Paints Solvent Thinnable Primer or Water Thinnable Supra Acrylic Cement Primer and allow drying for 6-8 hours. Sand the surface with emery paper no.320 and wipe clean.

Top Coat:

Thin 1ltr. of Shingar All Rounder with 500 ml of water. Apply 2-3 coats of this thinned paint with gap of 6-8 hrs. in between two coats.

For Exterior Application:

Putty:

Surface imperfections like holes, dents and cracks are to be filled with British Paints Cement Based Wall Putty.

Primer:

Apply one coat of British Paints Supra Acrylic Exterior Wall Primer by thinning with water in the ratio of 2:1 by volume. Allow primer to dry for atleast 6-8 hours.

Top Coat:

Apply 2-3 coats of Shingar All Rounder by diluting 1ltr. of Shingar All Rounder with a maximum of 400 ml of water. Keep an interval of 6-8 hours in between two coats.

Points To Remember:

Stir well before use. For details on the performance warranty refer to our product catalogs or log on to www.britishpaints.in. For dark shades an extra coat of Shingar All Rounder may be required to get better hiding. Keep the container closed when not in use.

(The information herein is given in good faith. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface)

(Please note that this product technical data sheet supersedes all previous versions.)

FOR MORE ENQUIRY

19 D.D.A. Commercial Complex, Kailash Colony Extn. Zamrudpur, New Delhi-110048
Ph.: 011- 29240394-0396, 29231992, E-mail: sales@britishpaints.in

TOLL FREE ☎ 1800-111-300

☎ +91 8882022255

www.britishpaints.in

Also Follow us on —



BritishPaints



British_Paints



company/British-Paints