

SHINGAR SMART

EXTERIOR EMULSION

British Paints
Celebrating 100 Years

Shingar Smart Exterior Emulsion is an Acrylic Co-polymer emulsion based wall coating for exteriors. Its unique formulation ensures that the product has excellent adhesion to different types of surface like cement, plaster, asbestos etc. Once the film dries hard, it exhibits excellent resistance to chalking, cracking and weathering in comparison to cement paint. Shingar Smart Exterior Emulsion gives clean and non-fading shades, ensuring long lasting performance much better than cement paint shades. It offers good anti-algal properties in dry to moderately humid climatic condition. However, it may not completely prevent the growth of black algal spots in areas with excessive rainfall or coastal belts.



TECHNICAL DATA

Areas of application	:	Cement Plaster, Asbestos Sheet, Concrete etc.
Consistency	:	Smooth and Free-Flowing
Thinner	:	Municipal / Potable Water
Thinner	:	60% by volume with water for each coat
Method of application	:	Brush/Roller
Drying time	:	Touch dry in 30 minutes
Recoating period	:	About 4-6 Hrs
Coverage on normal	:	Rough Cement Plaster 55-60 sq. ft. / ltr / 2 coats
Finish	:	Smooth and Matt
Shade available	:	As per shade card
Packs available	:	20ltr, 10ltr, 4ltr & 1ltr

DIRECTIONS FOR USE

- The surface to be painted should be cleaned of all loose paint, dust, grease and fungus or algae growth
- Only using cement plaster should fill imperfections of the surface
- Shingar Smart Exterior Emulsion should be applied by thinning 1 ltr of paint with 400 ml. of water with a gap of 4-6 hours between coats
- Use of Shield/British White Cement Based Wall Putty and Acrylic Exterior Wall Primer is recommended to set a Smooth and Better finish
- Shingar Smart Exterior Emulsion can be applied by brush or roller

(The information herein is given in good faith. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface)



SHINGAR SMART EXTERIOR EMULSION