

# ALL PURPOSE WHITE PRIMER

British Paints All Purpose White Primer is a solvent thinnable primer which is meant for all kind of surfaces including interior walls, wooden surfaces and metal surfaces.



## TECHNICAL DATA

Method of application	: Brushing
Thinner Recommended	: British Paints G.P Thinner
Application Viscosity	: 30-40 Sec
Covering capacity (Spreading By Brushing)	: 130-145 Sq Ft/ Ltr / Coat
Drying Time	: Surface Dry – Maximum 1 Hrs. [28-30°C & 60±5% r.h.] Hard Dry – Not more than 24 hrs.
Recoating Period	: 6-8 Hours
Flash Point	: Above 35 Degree C
Shade	: White
Packs Available	: 20 Liter, 10 Liter, 4 Liter, 1 Liter, 500 Milliliter

## DIRECTION FOR USE

### SURFACE PREPARATION

Sand the surface with emery paper no. 180 to remove loose particles, paint, dust, cracked & flaked paint and wipe clean.

### PRIMER

Apply a coat of All Purpose White Primer after thinning (up to maximum of 10%) with British Paints G.P Thinner and allow drying for 6-8 hours.

### PUTTY

Smoothen the surface by filling dents with a thin coat of British Paints Acrylic Wall Putty (in case of interior walls and wooden surfaces) Or Knifing Paste Filler (in case of metal surfaces). And allow drying for 4-6 hours. Sand the surface with emery paper no.180 and wipe clean.

### PRIMER

Apply another coat of British Paints All Purpose White Primer and allow drying for 6-8 hours. Before application of topcoat, sand the surface with emery paper no.320 and wipe clean.

(The information given herein is given in good faith. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface.)



ALL PURPOSE WHITE PRIMER