

EXPA 2 in 1 PREMIUM EXTERIOR EMULSION

Expa 2 in 1 is a 100% acrylic high built exterior paint made to international standards that keeps exteriors looking bright and new for many years. Expa 2 in 1 provides the dual protection i.e. it protects the surface from extreme heat and rains due to presence of Anti Sun and Anti Rain formula. Expa 2 in 1 is a high performance architectural coating for all types of construction residential building, offices and commercial complexes. Expa 2 in 1 is a 100% pure acrylic emulsion, with tough adhesion and flexibility, its light fast chemical resisting pigments and other special additives, provides protection against alkali, U.V. degradation, fungal and algae growth.



TECHNICAL DATA

Areas of application	:	Cement Plaster, Concrete Stone, Brick Asbestos, Cement Sheet & all types of Building Boards
Caution	:	Not recommended on lime wash
Viscosity of supply	:	10 ± 2 Ps/ Rotothinner / 30°C
Thinner	:	Municipal / Potable Water
Thinner ratio	:	Paint : water 100 : 40 by volume for each coat
Method of application	:	Brush / Roller
Primer	:	On highly absorbent or chalky surface, apply a coat of Expa 2 in 1 thinned with water (1: 1 by volume) as a self-priming coat or Exterior Wall Primer to reduce surface porosity and thereby reducing the degree of absorption of subsequent finish coats
Spreading capacity	:	60-65 sq. ft. / ltr / 2 coat
Drying time	:	Surface dry maximum 1 Hrs. (28- 30°C & 60 ± 5%R.H.) Re-coating period minimum 4 Hrs.
Finish	:	Smooth & Matt
Shades available	:	As per shade card
Packs available	:	20 ltr, 10 ltr, 4 ltr & 1 ltr

DIRECTIONS FOR USE

Performance of Expa 2 in 1 Exterior Emulsion critically depends on surface preparation and application as outlined below:

- Newly plastered surface should be painted with Expa 2 in 1 only after 2-3 month of curing of plasters.
- Before painting, ensure that the surface is free from dust, loose / chalky particles, fungus, algae etc.
- Previously painted surface with oil paint should be sanded thoroughly to make surface dull and matt for better adhesion, Surface previously coated with cement paint should be wire brushed and washed with water.
- Apply the first coat thinned at recommended dilution on moistened surface. Allow drying for minimum of 4 hours under normal weather condition before applying the second coat at the same dilution.
- Expa 2 in 1 Exterior Emulsion can be brushed or rolled.

Note: Cooling of surface upto 5° C is applicable for white and light shades only.

(The information herein is given in good faith. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface).

