



TECHNICAL DATA


Areas of Application	: All types of plasters, hard boards, false ceiling, asbestos sheets & concrete
Viscosity of Supply	: 11 to 15 ps by rotothinner at 30°C
Method of Application	: Brush / Roller
Thinner Recommended	: Municipal / Potable Water
Application Viscosity for Brushing	: Supply viscosity can be thinned with 2-3% of recommended thinner (if necessary) depending on surfaces.
For Spraying / Roller	: Application viscosity is to be adjusted with recommended thinner
Covering Capacity	: 150-170 sq. ft. / ltr / 2 coats (Depending on the shade and the texture of surface)
Drying Time	: Surface dry time 5-10 minutes (@28-30°C & 60 ± 5% R.H.) Re-coating period 3-4 Hrs.
Finish	: Smooth Matt with Slight sheen
Shades	: As per Shade Card

GLAMOUR PREMIUM ACRYLIC EMULSION



Glamour Premium Acrylic Emulsion is the choice paint for the beautiful interior of a dream home, available in the widest range of mood creating shades. It dries rapidly and is perfectly washable to give the walls a freshly painted look year-after-year. Its characteristic sheen helps in reducing dirt pick-up and gives the walls a rich finish. Based on a highly durable pure acrylic binder, Glamour Premium Acrylic Emulsion provides long lasting protection to interiors. It is characterized by excellent flow, leveling, opacity and smooth finish and has excellent anti-fungal properties.

PRODUCT FEATURES



PACKS AVAILABLE



HOW TO APPLY

Performance of Glamour Premium Acrylic Emulsion depends on surface preparation & application as outlined below.

Surface Preparation

New plaster:- It is advisable to allow new plaster surfaces to mature for a period of at least 6 months after the application of a recommended coat of lime wash to ensure thorough drying of plaster. Remove loose particles and paint flakes. Rub with sand paper to ensure that the surface is dry and free from dust, dirt grease etc. In case of repainting job previous coating of lime wash, powder, distemper etc. must be thoroughly scraped off. Earlier coating of oil based distemper or emulsion based paint need not be removed if in sound condition. However, the gloss or sheen of such coatings must be removed by thorough sanding, cracked or flaked paints must be removed completely, fungus affected areas need separate adequate treatment. Repair the cracked portion of plaster and areas affected by leaks, drainage etc. well prior of painting. Allow the surface to dry sufficiently.

Application

For repainting:- Use British Paints Acrylic Cement Primer (Water Thinnable) as a priming coat. For new surface, British Paints Solvent Thinnable Primer as priming coat is recommended. This will take care of excessive absorption and alkalinity of walls. For best results, fill the dents and smoothen the undulation of wall by applying British Paints Acrylic Wall Putty. Wherever application of Putty is resorted, a coat of British Paints Solvent Thinnable Primer is highly recommended, on the top of Putty as undercoat to eliminate patchy appearance of finish coat. Tinting of Putty approximately close to the final finish with Xtratone Universal Stainer recommended for flawless appearance and improved coverage. Wherever solvent thinnable primer is used, allow it to dry overnight before finishing coat. For protected areas like balcony, porticos, porches, yearnings etc. avoid use of plaster of paris or its admixture to fill dents and imperfections.

(The information herein is given in good faith. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface)

(Please note that this product technical data sheet supersedes all previous versions.)