

SHINGAR MAX SUPERIOR EXTERIOR EMULSION

Shingar Max is a water based 100 % Acrylic Exterior wall finish which is suitable for dry or moderately humid climatic conditions.



TECHNICAL DATA

Areas of Application	:	Cement Plaster, Asbestos Sheet, Concrete etc.
Viscosity of Supply	:	100-112 Krebs Units on Stormier Viscometer at 30°C
Consistency	:	Smooth and Free-Flowing
Thinner	:	Municipal / Potable Water
Thinner Ratio	:	75% by volume with water for each coat
Method of Application	:	Brush / Roller
Drying Time	:	Touch Dry in 30 minutes. Recoating period about 4-6 Hrs.
Coverage on normal to rough cement plaster	:	55-65 sq. ft. / ltr / 2 coats
Finish	:	Smooth and Matt
Shades available	:	As per shade card
Packs available	:	20 ltr, 10 ltr, 4 ltr & 1 ltr

DIRECTIONS FOR USE

- The surface to be painted should be cleaned of all loose paint, dust grease and fungus or algae growth
- Only using cement plaster should fill imperfections of surface
- Shingar Max should be applied by thinning 1 ltr of paint with 400 ml. of water with a gap of 4-6 hours between coats
- Use of Shield/British White Cement Based Wall Putty and Acrylic Exterior Wall Primer is recommended to set a smooth and better finish
- Shingar Max can be applied by brush or roller

(The information herein is given in good faith. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface).

SHINGAR MAX SUPERIOR EXTERIOR EMULSION

