

# SHEER CLASS SPLENDOR LUXURY INTERIOR EMULSION

British Paints Splendor is a water based, 100% Acrylic Interior Wall finish which gives your walls high sheen, excellent scrub resistance & a truly luxury finish.



## TECHNICAL DATA

Areas of application	:	All types of plasters, hard boards, false ceiling, asbestos sheets & concrete
Consistency	:	Thick and Buttery
Thinner	:	Municipal / Potable Water
Method of application	:	Brush / Roller
Spreading capacity	:	140-160 sq. ft. / ltr / 2 coats (Actual coverage may vary depending on method, condition of application, surface porosity and shade)
Drying time	:	Surface dry time 15-25 minutes
Finish	:	Smooth Matt with Slight Sheen
Shades available	:	As per shade card (Refer to Colormenu fendeck)
Packs available	:	20 ltr, 10 ltr, 4 ltr & 1 ltr

## DIRECTIONS FOR USE

**Surface Preparation:** Sand the surface with emery paper no. 180 to remove loose particles, paint, dust, cracked & flaked paint and wipe clean.

**Primer:** Apply a coat of British Paints Solvent Thinnable or Water Thinnable Acrylic Cement Primer (for repairing use Water Thinnable Acrylic Cement Primer and for new surface Solvent Thinnable Primer is recommended) and allow drying for 6-8 hours.

**Putty:** Smoothen the surface by filling dents with a thin coat of British Paints Acrylic Wall Putty and allow drying for 4-6 hours. Sand the surface with emery paper no. 180 and wipe clean.

**Primer:** Apply another coat of British paints Solvent Thinnable Primer or Water Thinnable Acrylic Cement Primer and allow drying 6-8 hours. Sand the surface with emery paper no. 320 and wipe clean.

**Top Coat:** Thin 1 litre of Splendor with 400-500 ml of water. Apply 2-3 coats of this thinned paint with a gap of 3-4 hours in between two coats.

## POINTS TO REMEMBER

For details on the performance warranty, refer to our product catalogue or log on to [www.britishpaints.in](http://www.britishpaints.in)

For dark shades an extra coat of Sheer Class Splendor may be required to get better hiding.

Stir well before use.

Keep the container closed when not in use.

